

**IKO****TECHNICAL DATA SHEET****STOCK NO. 0670020****January, 2013****AM #15 ASPHALT FELT**

This product consists of a resilient, high-strength cellulose fiber mat that has been saturated with premium waterproofing bitumen to produce AM #15 Asphalt Felt, a superior building material used specifically as a residential roofing underlayment. AM #15 Asphalt Felt meets the requirements of the Canadian National Building Code section 9.26.6.1-1a. IKO's roofing products are produced and designed with consideration for environmental responsibility and sustainability, incorporating quality recycled components whenever possible, manufactured in facilities that comply with the most stringent government environmental regulations, and can therefore be a part of any "green" construction project.

<b>CHARACTERISTIC</b>	<b>UNITS</b>	<b>NOMINAL VALUE</b>	<b>TEST METHOD</b>	<b>STANDARD LIMITS</b>
<b>QUANTITY PER PALLET:</b>	-	36	-	N/A
<b>PALLET SIZE:</b>	cm (in)	107 x 107 (42 x 42)	-	-
<b>LENGTH:</b>	m (ft)	43.9 (144)	-	±0.1%
<b>WIDTH:</b>	mm (in)	914 (36)	-	±3 (1/8)
<b>LINES:</b>	mm (in)	1 <sup>st</sup> - 51 (2) 2 <sup>nd</sup> - 216 (8 ½) 3 <sup>rd</sup> - 432 (17)	-	±6 (1/4)

*The information on this Technical Data sheet is based upon data considered to be true and accurate, based on laboratory tests and production measurements, and is offered solely for the user's consideration, investigation and verification. Nothing contained herein is representative of a warranty or guarantee for which the manufacturer can be held legally responsible. The manufacturer does not assume any responsibility for any misrepresentation or assumptions the reader may formulate.*